



Portal > Knowledgebase > Satellite Wi-Fi Hotspots > Inmarsat IsatHub > iSavi Inmarsat IsatHub Terminal Firmware Update

iSavi Inmarsat IsatHub Terminal Firmware Update

Chuck Reisinger - 2019-02-20 - in Inmarsat IsatHub

Follow the instructions below to update to the most recent firmware version on the iSavi IsatHub Terminal.

1. Download and unzip the firmware file to a folder on your computer ([Download](#))
2. With the SIM card inserted, power on the iSavi IsatHub terminal.
3. Once the terminal is powered on, connect the iSavi Wi-Fi network with a laptop or desktop computer. The Wi-Fi name (SSID) and password are listed on a label on the bottom of the iSavi terminal.
4. Once connected to the iSavi Wi-Fi network, open a web browser and enter **192.168.1.35** into the address bar.
5. Within a minute you should see a login screen. Login with username: **admin**, and default password either 1234 or 123456.
6. Once you are logged into the panel select **Settings > Terminal Settings > Firmware Upgrade**.

HOME DATA ▼ TELEPHONY ▼ SMS ▼ SETTINGS ▼

Home IsatHub

Status:
Registered to network - **No**
Data connection active - **No**

Register Network

Signal:
0 dB

Terminal pointing angle	
Elevation	Azimuth
48.03°	203.75° SSW

Satellite **AMFR**

- Accounts
- Wi-Fi
- Security
- Terminal Settings
- Terminal Info
- Language
- Support

7. Click the **Firmware Upgrade** button. The terminal will reboot into the Firmware Upgrade Mode.

Firmware Upgrade

Need to reboot in the Firmware Upgrade Mode (Safe Mode). Please do it manually if reboot failed.

Firmware Upgrade

Disclaimer

Please be informed that firmware upgrading is done at your own risk and the equipment manufacturer will not be held responsible for any possible malfunction or damage to the system due to upgrading the firmware.

If you encounter any problems or have any questions, please contact the equipment distributor for technical support.

8. Once the unit reboots you will need to log on to the Wi-Fi connection again.

9. Once logged in, go to **192.168.1.35** in your browser and login to the web console again.

10. Click the **Choose File** button to select the firmware file saved on your computer, then click to the **Upload** button.

Firmware Upgrade iSavi™

New Firmware package to upload: No file chosen

Disclaimer

Please be informed that firmware upgrading is done at your own risk and the equipment manufacturer will not be held responsible for any possible malfunction or damage to the system due to upgrading the firmware.

If you encounter any problems or have any questions, please contact the equipment distributor for technical support.

11. Your screen will show the status of the upload. Once the upload completes the unit will reboot and be ready for use.